



Connect Modular



7559 Nesting



7569 Spirituality



7655 Incentive-ize




7676 Authenticity



7681 Next Gen



7729 Younique




7821 Invent



7828 Flex




7858 Define



7956 Life Shopping



7978 Connecting



7989 Personalize

PRODUCT SPECIFICATIONS

Style Name.....	Connect Modular	Secondary Backing .....	Fiberglass Reinforced Thermoplastic Composite
Product Type .....	Modular	Pattern Repeat.....	Not Applicable
Construction .....	Tufted	Size.....	24" x 24" (.6096 m x .6096 m)
Surface Appearance .....	Textured Patterned Loop	Recycled Content .....	Minimum 35% pre-consumer by total weight
Nylon Type.....	Colorstrand® SD Nylon	Flammability .....	ASTM E 648 Class 1 (Glue Down)
Gauge .....	1/10 (39.37 rows per 10 cm)	Smoke Density .....	ASTM E 662 Less Than 450
Pile Weight .....	24.0 oz. per sq. yd. (814 g/m <sup>2</sup> )	Static Propensity.....	AATCC-134 Under 3.5 KV
Pile Thickness.....	.146" (3.71 mm)	IAQ Green Label.....	39901930
Stitches Per Inch .....	10.7 (42.13 per 10 cm)	IAQ Green Label Plus.....	3990
Dye Method.....	Solution Dyed	CRI Rating.....	Severe Traffic
Protective Treatment.....	Sentry Plus	Warranties: Lifetime Encycle Modular Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static	
Density .....	5,918		
Weight Density.....	142,032		
Primary Backing.....	Reinforced Synthetic		
Bonding Agent.....	100% PVC-Free Thermoplastic		
Backing Foundation .....	Encycle® Modular by Bigelow		