



Rapid Transit Modular



7565 Destination




7575 Arrival




7652 Subway




7812 Non-Stop



7848 Turnstile



7853 Token



7856 Easy Exit



7876 Departure



7878 Supersonic



7948 On Time



7968 On Board



7988 Schedule

PRODUCT SPECIFICATIONS

Style Name.....	Rapid Transit Modular
Product Type.....	Modular
Construction.....	Tufted
Surface Appearance.....	Textured Multi Colored Loop
Nylon Type.....	Colorstrand® Nylon
Gauge.....	1/10 (39.37 rows per 10 cm)
Pile Weight.....	22.0 oz. per sq. yd. (746 g/m ²)
Pile Thickness.....	.127" (3.23 mm)
Stitches Per Inch.....	10.5 (41.34 per 10 cm)
Dye Method.....	Solution Dyed/Space Dyed
Protective Treatment.....	Sentry Plus
Density.....	6,236
Weight Density.....	137,192
Primary Backing.....	Reinforced Synthetic
Bonding Agent.....	100% PVC-Free Thermoplastic

Backing Foundation.....	Encycle Modular by Bigelow
Secondary Backing.....	Fiberglass Reinforced Thermoplastic
.....	Composite
Recycled Content.....	Minimum 35% pre-consumer by total weight
Pattern Repeat.....	Not Applicable
Size.....	24" x 24" (.6096 m x .6096 m)
Flammability.....	ASTM E 648 Class 1 (Glue Down)
Smoke Density.....	ASTM E 662 Less Than 450
Static Propensity.....	AATCC-134 Under 3.5 KV
IAQ Green Label.....	39901930
IAQ Green Label Plus.....	3990
CRI Rating.....	Severe Traffic
Warranties: Lifetime Limited Encycle Modular Warranty, Lifetime Static	